

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1(Currently amended). A system for distributing program services by transmitting said program services in the form of a plurality of audio/video signals from a headend facility to a plurality of receiving devices ~~detecting the presence of a remote device~~, the system comprising:

a primary device for receiving and distributing the plurality of audio/video signals from said headend facility and including having a wireless accessory for wireless communication with at least one remote device to distribute said audio/video signals ~~detecting the presence of at least one remote device~~, wherein the primary device determines ~~the presence of the at least one remote device by determining~~ a distance between the primary device and each remote devices~~[[,]]~~ via the wireless accessory, ~~wherein when the primary device determines and facilitates disablement of said program services to each remote device with said determined the distance to be within from said primary device exceeding a predetermined distance, the remote device continues to receive signals.~~

2(Currently amended). The system of claim 1, wherein when the primary device determines the distance to be outside of the predetermined distance, the corresponding remote device discontinues receiving signals.

3(Currently amended). The system of claim 1, wherein the primary device receives a proximity detection request from [[a]] the headend facility, and, in response, the primary device transmits a signal indicating the presence or absence of the at least one remote device within the predetermined distance.

4(Currently amended). The system of claim 3, wherein when the headend facility receives the signal indicating the absence of the at least one remote device, the headend facility discontinues program services to the at least one remote device.

5(Currently amended). The system of claim 4, wherein the headend facility discontinues program services by at least one of no longer transmitting signals directly from the headend facility and sending a discontinue signal to the primary device directing the primary device to no longer communicate with the at least one remote device.

6(Original). The system of claim 1, wherein the primary device includes a set-up procedure that includes detecting and storing the distance between the primary device and the at least one remote device, wherein the detected distance becomes the predetermined distance.

7(Original). The system of claim 1, wherein the primary device determines the distance by using a receive signal strength indication measurement.

8(Currently amended). The system of claim 1, wherein the primary device determines the distance by using ultrawideband (UWB) communications with the at least one remote device.

9(Currently amended). A system for distributing program services by transmitting said program services in the form of a plurality of audio/video signals from a headend facility to a plurality of receiving devices, the system comprising:

a primary device for receiving and distributing the plurality of audio/video signals from said headend facility, the primary device comprising:

a plurality of tuners, each tuner for providing an audio/video signal; and

a wireless accessory for wireless communication to distribute said audio/video signal from each said tuner; and

at least one remote device in wireless communication with the primary device to receive said program services, the at least one remote device for selecting and receiving a selected audio/video signal from at least one of the plurality of tuners and the headend facility[.];

wherein the primary device determines ~~wireless accessory detects one of the~~ presence and absence of the ~~at least one remote device by determining~~ a distance between the primary device and the ~~at least one each said~~ remote device via the wireless accessory; ~~wherein when the primary device determines and facilitates disablement of said program services to each remote device with said determined the distance to be within from said primary device exceeding a predetermined distance, the at least one remote device continues to receive audio/video signals.~~

10(Currently amended). The system of claim 9, wherein when the primary device determines the distance to be outside of the predetermined distance, the ~~at least one~~ corresponding remote device discontinues receiving signals.

11(Currently amended). The system of claim 9, wherein the primary device receives a proximity detection request from ~~[[a]]~~ the headend facility, and, in response, the primary device transmits a signal indicating the presence or absence of the at least one remote device within said predetermined distance.

12(Currently amended). The system of claim 11, wherein when the headend facility receives the signal indicating the absence of the at least one remote device, the headend facility discontinues program services to the at least one remote device.

13(Currently amended). The system of claim 12, wherein the headend facility discontinues program services by at least one of no longer transmitting signals directly from the headend facility and sending a discontinue signal to the primary device directing the primary device to no longer communicate ~~communication~~ with the at least one remote device.

14(Original). The system of claim 9, wherein the primary device includes a set-up procedure that includes detecting and storing the distance between the primary device and the at least one remote device, wherein the detected distance becomes the predetermined distance.

15(Original). The system of claim 9, wherein the primary device determines the distance by using a receive signal strength indication measurement.

16(Currently amended). The system of claim 9, wherein the primary device determines the distance by using ultrawideband (UWB) communications with the at least one remote device.